

pakmix[®] *pro line*

QUALITY PACKAGED CONCRETE PRODUCTS NATIONWIDE

Description:

PAKMIX[®] Cement Fortifier is a liquid acrylic polymer for dramatically improving the flexural, compressive and impact strength of concrete. PAKMIX Cement Fortifier increases adhesion of new cements, grouts, and mortars to older masonry surfaces and reduces the possibility of cracking and spalling due to premature drying.

Suggested Uses:

- ▶ Add integrally to cement mixes or cement coatings.
- ▶ Excellent for mixing sand-topping mix to resurface concrete.
- ▶ Use as an admix with thin set.

Preparation:

All surfaces must be structurally sound and free of any oil, gas, grease, paint, etc., before applying the fresh cement mix.

Simply add:

- ▶ PAKMIX[®] Cement Fortifier at the rate of one part Fortifier to three parts clean water.
- ▶ For more strength, add more Cement Fortifier in place of water.

Packaging & Yields:

One gallon (1 gal.) will mix up to approximately 300 pounds of concrete or 250 pounds of mortar or grout. A higher concentration of PAKMIX Cement Fortifier will mix less material.

Packaged in 1 qt., 1 gal. and 5 gal. plastic containers.

For Best Results:

Add PAKMIX[®] Cement Fortifier to water; then add the liquid mixture to the dry cement material.

Use only when temperature is 50° F and rising.

Clean Up:

Clean up is easy with soap and water. Rinse tools before material hardens.



Caution:

PAKMIX[®] Cement Fortifier contains a water-based acrylic polymer. Avoid contact with skin. Wear protective clothing, gloves and eye protection when working with cement. If any material gets into the eyes, rinse immediately and contact a physician if swallowed. Wash exposed skin areas promptly with water. Do not take internally.

Keep Out of Reach of Children:

Material Safety Data Sheet available upon request.

Keep From Freezing.



C E M E N T F O R T I F I E R

pakmix[®] *pro line*