

**pakmix**<sup>®</sup> pro line

QUALITY PACKAGED CONCRETE PRODUCTS NATIONWIDE

**Description:**

**PAKMIX<sup>®</sup> Concrete Glue** is a liquid bonding adhesive for improving the bond between new Portland cement mixes and existing surfaces. Easily applied by brush, roller or spray.

**Suggested Uses:**

- ▶ Bond new concrete to old concrete and masonry.
- ▶ Improve holding power of new stucco or mortar to any interior or exterior clean, sound surface.
- ▶ Bond mortar bed for ceramic tile to old floors and walls.

**Preparation:**

All surfaces must be structurally sound and free of oil, gas, grease, etc., before applying PAKMIX<sup>®</sup> Concrete Glue. All glossy painted surfaces should be dulled. Paint should be at least 60 days old, not water-base and firmly applied to substrate. Stir PAKMIX<sup>®</sup> Concrete Glue before applying – do not shake. Apply a small test patch if surface is questionable. Allow it to dry completely, then check to make sure there is no peeling or curling.

**Items you may need:**

- ▶ Roller.
- ▶ Paint Brush.

**Packaging & Yields:**

One gallon (1 gal.) covers approximately 200-300 sq. ft. depending on porosity and texture of surface.

Packaged in 1 qt. and 1 gal. plastic containers.

**For Best Results:**

Use only when temperature is 50° F and above. Surface to be covered should be damp, not soaking wet. PAKMIX<sup>®</sup> Concrete Glue is ready to use – do not thin. When applying concrete toppings, apply at least 1/2" thick. (*Toppings containing water may be applied when bond is tacky or dry*) Other materials should be applied only when bonding is still tacky (20 to 60 minutes). When bonding finish plaster; be sure the base coat is dry.

**Clean Up:**

Clean up is easy with soap and water. Rinse tools before material hardens.

**Caution:**

Contains Ethylene Glycol and PVA emulsion. Avoid contact with skin and breathing of vapors. Wear protective clothing, gloves and eye protection when using the product. Wash exposed skin areas promptly with water. Do not take internally. Contact a physician if swallowed.

**Keep Out of Reach of Children:**

Material Safety Data Sheet available upon request.

**Keep From Freezing.**



CONCRETE GLUE

**pakmix**<sup>®</sup> pro line