

pakmix[®] pro line

QUALITY PACKAGED CONCRETE PRODUCTS NATIONWIDE

Description:

PAKMIX[®] Post Mix is designed to be used for setting posts and poles. The blend of cement, sand and gravel is thoroughly premixed for ease of use.

Suggested Uses:

Setting:

- ▶ Mailboxes
- ▶ Fence Posts
- ▶ Basketball/Game Posts
- ▶ Lamp Posts
- ▶ Swing Sets

Directions for Mixing:

Place the entire contents of the bag in a wheelbarrow, mixing tub or cement mixer. Add water slowly and mix to a smooth, stiff consistency using a shovel or mixing hoe.

Items you may need:

- ▶ Wheelbarrow, mixing tub or cement mixer.
- ▶ Post Hole Digger
- ▶ Shovel and Mixing Hoe
- ▶ Measuring Tape

Packaging & Yields:

50 lb. bag 1/2 cu. ft. fills a hole
12" to 16" diameter 6" to 8" deep.

80 lb. bag 2/3 cu. ft. fills a hole
12" to 16" diameter 8" to 11" deep.

All yields are approximated.

For Best Results:

Use only when temperature is 40° F and above. In cold weather use warm – not hot water for mixing. Do not use when freezing temperature is forecast.

A general rule is to have the hole 4" deep for every one (1') foot of post that is above grade. (Example: for a post this is 4 feet above grade, the hole should be 16 inches deep) The diameter of the hole should be three to four (3-4) times the width of the post. (Example: for a 4 x 4 post, the diameter should be 12" to 16".)

When setting posts for high activity equipment, swing sets, basketball, or volleyball posts, always follow the manufacturer's suggested post hole size.

Place 4" to 6" of gravel in the bottom of the hole before setting the post. Lightly dampen the hole before pouring the mix and setting post.

The top of the concrete at the base of the post, should slope away from the post to allow surface water to drain.

Use a temporary brace to insure the post is plumb and remains undisturbed during the curing process. The newly set post should not be disturbed for at least 72 hours.

For faster setting times, use PAKMIX[®] Fast Setting Accelerator.

Clean Up:

Clean up is simple and easy with soap and water. Rinse tools before material hardens.

Caution:

PAKMIX[®] Post Mix contains Portland cement. As with any cement materials, direct contact may irritate eyes and skin. Wear protective clothing, gloves and eye protection when using the product. If any material gets into the eyes, rinse immediately and contact a physician. Wash exposed skin areas promptly with water. Do not take internally.

Warning Inhalation Hazard: Avoid inhalation of dust from this product, which contains crystalline silica that causes lung disease and cancer. Use with mechanical ventilation or respiratory protection (dust mask).


Keep Out of Reach of Children:

Material Safety Data Sheet available upon request.



**P
O
S
T

M
I
X**



POST MIX

pakmix[®] pro line

605 Industrial Way, Dixon, California 95620 • (800) 272-5649 • FAX (707) 693-9349

www.pakmix.com